

LD-15 WATER LEAK DETECTOR



KEY FEATURES

- 1 Amplifier w/meter display & filter controls
- 2 Aviation-grade stereo headphones
- 3 High sensitivity sensor & cable
- 4 Padded case & waist strap

FEATURES

- ▷ High sensitivity sensor with Neodymium magnet (extra strong). Sensor and cable connection completely sealed and water-proof (submersible).
- ▷ Amplifier with superior audio quality (very low distortion and superior signal-to-noise ratio) and large meter display. Press the Mute Switch to hear sounds when you are ready.
- ▷ “Survey” for water leaks by listening at hydrants and valves with the sensor and magnet. Survey at water meters with a Long Contact Rod (optional).
- ▷ “Pinpoint” water leaks in pipes under asphalt or concrete with the base plate attached to the sensor and magnet.
- ▷ Use the High filter range for water leak surveying. Use the Low filter range for water leak pinpointing. High frequency leak sounds travel on the pipes, but only low frequencies pass through the soil.

SPECIFICATIONS

AMPLIFIER

- ▷ Amplification: 56 dB
- ▷ Filter Ranges:
 - 1) High Range: 30 Hz to 5000 Hz
 - 2) Low Range: 30 Hz to 800 Hz
 - 3) Notch Filter: 150 Hz, 180 Hz
- ▷ Power: 4 “C” dry cell batteries
- ▷ Battery Life: 80 hours with alkaline batteries at 68° F
- ▷ Weight: 31 ounces (including batteries)
- ▷ Size: 6.4”w x 3.0”h x 5.7”d (163mm x 76mm x 144mm)

SENSOR

- ▷ Sensitivity: 10 V/g
- ▷ Resonance Frequency: 950 Hz (±150 Hz)
- ▷ Weather Protection: IP68 or equivalent (3 ft under water for 3 hours)
- ▷ Cable Length: 9.75 ft



Soft Case

- ▷ Padded custom case
- ▷ Standard belt (40 inches)



Includes:

- ▷ ABS custom case
- ▷ Instruction manual



SubSurface Instruments, Inc. | 1230 Flightway Drive, De Pere, WI. 54115
 toll free: 855.422.6346 | Website: www.ssilocators.com | email: info@ssilocators.com

