



DBS-20C

Mid-Range Squeeze Tool

2" IPS Dual Bar

The redesigned Mustang Model DBS-20C Mid-Duty Squeeze Tool accommodates pipe sizes from 1/2" CTS to 2" IPS maximum. The DBS-20C can be used on service size pipe up to medium size distribution pipe with ease and safety. The lower jaw has two sets of gap stops to accommodate two pipe sizes of your choice.

Features include a larger, heavy-duty frame designed to withstand the greater force needed to squeeze today's PE pipe, while retaining the double bar jaw design for greater contact area.

A high-strength power screw and thrust bearing with grease fittings for lubrication, as well as a provision for using a SEG-30 Grounding Rod for static electric grounding, completes the package.

Weight: 15lbs
 Dimensions: 13.5" Height
 Capacity: Specify (2) Sizes (see table)

Pipe Size	Nominal Wall Thickness	SDR	Gap Stop	%Max Squeeze
IPS 1/2"	.090	9.3	.155	14
CTS 1/2"	.090	7	.147	22
	.104	6	.172	21
IPS 3/4"	.095	11	.155	25
CTS 3/4"	.090	9.7	.155	18
IPS 1"	.119	11	.210	22
	.140	9.3	.234	27
CTS 1"	.090-.101	11-12.5	.155	29
IPS 1-1/4"	.151-.166	10-11	.270	27
	.178	9.3	.288	25
CTS 1-1/4"	.090	15	.155	17
	.121	11	.210	19
IPS 1-1/2"	.173	11	.288	22
IPS 2"	.216	11	.347	25