



Weight: 45lbs  
 Dimensions: 20" Height  
 Capacity: Specify (4) Sizes (see table)

# DBS-44F

## Mid-Range Squeeze Tool

### 4" IPS Quad-Bar

The DBS-44F is similar to the DBS-40F but uses a four bar design that accommodates wide range of large PE pipe sizes from 1" IPS to 4" IPS. The quad-bar lower jaw has four sets of gap stops for the four pipe sizes of your choice.

Features include a larger, heavy-duty frame designed to withstand the greater force needed to squeeze today's PE pipe, while retaining the double bar jaw design for greater contact area.

A high-strength Acme power screw and replaceable nut is powered with a 24" alloy steel handle. The unique Mustang designed thrust bearing and grease fitting, for lubrication, provides friction free force to the upper jaw.

Static electric grounding is accomplished by using an upper jaw grease fitting adapter.

Pipe Size	Nominal Wall Thickness	SDR	Gap Stop	%Max Squeeze
IPS 1"	.119	11	.210	22
	.140	9.3	.234	27
IPS 1-1/4"	.151-.166	10-11	.270	27
	.178	9.3	.288	25
IPS 1-1/2"	.173	11	.288	22
IPS 2"	.216	11	.347	25
	.255	9.3	.410	28
IPS 3"	.307-.318	11-11.5	.500	29
	.259	13.5	.435	26
IPS 4"	.395-.409	11-11.5	.675	26
	.333	13.5	.560	25